

# GA 15 G

|                                        |                      |
|----------------------------------------|----------------------|
| <b>Max. Working height</b>             | 14,95 m              |
| <b>Max. lateral reach</b>              | 9,80 m               |
| <b>Max. Basket load / Lifting load</b> | 215 kg               |
| <b>Overall dimensions LxWxH</b>        | 6.47 x 1.81 x 2.11 m |
| <b>Transport position length</b>       | 6,47 m               |
| <b>Construction width</b>              | 1,81 m               |
| <b>Transport position height</b>       | 2,11 m               |
| <b>Drive type</b>                      | 230V                 |
| <b>Dead weight</b>                     | 1620 kg              |
| <b>Max. Platform height</b>            | 12,95 m              |
| <b>Platform dimensions LxW</b>         | 1,30 x 0,70 m        |
| <b>Supports</b>                        | ja                   |
| <b>Support pressure max.</b>           | 13 kN                |
| <b>Support load</b>                    | 100 kg kg            |
| <b>Support width on both sides</b>     | 4,46 m               |
| <b>Support diagonal</b>                | -                    |
| <b>Support length</b>                  | 3,85 m               |
| <b>Ground clearance</b>                | 0,24 m               |
| <b>Rotating work basket</b>            | ja                   |
| <b>Basket arm, rotation angle</b>      | no-                  |
| <b>Indoor use only</b>                 | no                   |
| <b>Shunting drive</b>                  | ja                   |
| <b>Swivel range</b>                    | endless              |



