

## GG 209-24 AWkP

|  |   |
|--|---|
| <b>Max. Working height</b>             | 20,70 m   |
| <b>Movable up to working height</b>    | 20,70 m   |
| <b>Max. Pitch angle</b>                | 45%   |
| <b>Four-wheel drive</b>                | ja  |
| <b>Drive type</b>                      | Batterie  |
| <b>Non-Marking</b>                     | ja  |
| <b>Overall dimensions LxWxH</b>        | 8.48 x 2.41 x 2.49 m  |
| <b>Transport position length</b>       | 6,20 m  |
| <b>Construction width</b>              | 2,49 m  |
| <b>Transport position height</b>       | 2,98 m  |
| <b>Ground clearance</b>                | 0,29 m  |
| <b>Surplus</b>                         | 0,43 m  |
| <b>Dead weight</b>                     | 9475 kg   |
| <b>Track widening</b>                  | -   |
| <b>Platform dimensions WxD</b>         | 1.72 x 0.58 m   |
| <b>Max. Basket load / Lifting load</b> | 350 kg  |
| <b>Swing axle</b>                      | ja  |
| <b>Basket arm</b>                      | ja  |
| <b>Swivel range</b>                    | 355°  |
| <b>Rotating work basket</b>            | ja/2x90°  |
| <b>Max. lateral reach</b>              | 12,18 m   |
| <b>Special features</b>                | Fully all-terrain with battery drive, non-abrasive off-road tires, high basket load |



