

## GG 400-25 AQLPG

|                                        |                                                                                                                                                                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Max. Working height</b>             | 40,10 m                                                                                                                                                                                                                                                                               |
| <b>Movable up to working height</b>    | 40,10 m                                                                                                                                                                                                                                                                               |
| <b>Max. Pitch angle</b>                | 45 %                                                                                                                                                                                                                                                                                  |
| <b>Four-wheel drive</b>                | ja                                                                                                                                                                                                                                                                                    |
| <b>Drive type</b>                      | Diesel                                                                                                                                                                                                                                                                                |
| <b>Non-Marking</b>                     | no                                                                                                                                                                                                                                                                                    |
| <b>Construction width</b>              | 2,50 m                                                                                                                                                                                                                                                                                |
| <b>Overall dimensions LxWxH</b>        | 14.60 x 2.50 x 3.05 m                                                                                                                                                                                                                                                                 |
| <b>Ground clearance</b>                | 0,26 m                                                                                                                                                                                                                                                                                |
| <b>Transport position height</b>       | 3,05 m                                                                                                                                                                                                                                                                                |
| <b>Transport position length</b>       | 11,45 m                                                                                                                                                                                                                                                                               |
| <b>Surplus</b>                         | 3,55 m                                                                                                                                                                                                                                                                                |
| <b>Dead weight</b>                     | 20046 kg                                                                                                                                                                                                                                                                              |
| <b>Track widening</b>                  | 3,85 m                                                                                                                                                                                                                                                                                |
| <b>Platform dimensions WxD</b>         | 2.44 x 0.92 m                                                                                                                                                                                                                                                                         |
| <b>Max. Basket load / Lifting load</b> | 450 kg                                                                                                                                                                                                                                                                                |
| <b>Swing axle</b>                      | ja                                                                                                                                                                                                                                                                                    |
| <b>Basket arm</b>                      | ja                                                                                                                                                                                                                                                                                    |
| <b>Swivel range</b>                    | endless                                                                                                                                                                                                                                                                               |
| <b>Rotating work basket</b>            | ja                                                                                                                                                                                                                                                                                    |
| <b>Max. lateral reach</b>              | 20,25 m                                                                                                                                                                                                                                                                               |
| <b>Special features</b>                | Permanently installed generator for 230 V socket in the basket, high basket load, very favorable working diagram, short lifting and lowering times, basket boom can be swiveled horizontally and vertically, all-wheel steering, machine can be used on terrain inclines of up to 5°. |



