

# GL 16 N

|  |  |
|--|--|
| <b>Max. Working height</b>             | 16,29 m  |
| <b>Max. lateral reach</b>              | 10,40 m  |
| <b>Max. Basket load / Lifting load</b> | 250 kg   |
| <b>Platform dimensions LxW</b>         | 1,40 x 1,11 m  |
| <b>Overall dimensions LxWxH</b>        | 7.12 x 2.25 x 2.95 m   |
| <b>Support length</b>                  | 3,20 m   |
| <b>Support width on both sides</b>     | 2,29/2,34 m  |
| <b>Support width on one side</b>       | -  |
| <b>Vertical support width</b>          | -  |
| <b>Dead weight</b>                     | 3290 kg  |
| <b>Perm. total weight</b>              | 3500 kg  |
| <b>Drive type</b>                      | Diesel   |
| <b>Four-wheel drive</b>                | no   |
| <b>Ground clearance</b>                | 0,16 m   |
| <b>Rotating work basket</b>            | ja +/-90°.   |
| <b>Swivel range</b>                    | +/-200°  |
| <b>Basket arm</b>                      | no   |
| <b>Driving licence</b>                 | B / 3  |
| <b>Special features</b>                | Loading area 0.93 x 1.56 m with drop sides, box body for tools |





