

## GS 099-8 WI

|  |  |
|--|--|
| <b>Max. Working height</b>                   | 9,99 m   |
| <b>Movable up to working height</b>          | 9,99 m   |
| <b>Four-wheel drive</b>                      | no   |
| <b>Drive type</b>                            | Batterie   |
| <b>Non-Marking</b>                           | ja   |
| <b>Indoor use only</b>                       | ja   |
| <b>Overall dimensions LxW</b>                | 2,48 x 0,82 m  |
| <b>Construction width</b>                    | 0,82 m   |
| <b>Transport position height</b>             | 2,00 m   |
| <b>Transport height with/without railing</b> | 2,37 / 2,00 m  |
| <b>Ground clearance</b>                      | 0,07 m   |
| <b>Supports</b>                              | no   |
| <b>Dead weight</b>                           | 2230 kg  |
| <b>Platform dimensions LxW</b>               | 2,28 x 0,81 m  |
| <b>Platform length extended</b>              | 3,18 m   |
| <b>Swing axle</b>                            | no   |
| <b>Max. Lifting load on extension</b>        | 113 kg   |
| <b>Max. Basket load / Lifting load</b>       | 230 kg   |
| <b>Special features</b>                      | Attachment points for restraint systems (PPE) available! |

