

# GSA 25 H

<b>Max. Working height</b>	25,05 m
<b>Max. Basket load / Lifting load</b>	200 kg
<b>Drive type</b>	Hybrid
<b>Max. lateral reach</b>	15,61 m
<b>Overall dimensions LxWxH</b>	7.37 x 1.78 x 2.05 m
<b>Transport position length</b>	7,37 m
<b>Construction width</b>	1,78 m
<b>Transport position height</b>	2,05 m
<b>Platform dimensions WxD</b>	1.10 x 0.82 m
<b>Swing axle</b>	no
<b>Basket arm, rotation angle</b>	ja /90°
<b>Dead weight</b>	3000 kg
<b>Ground clearance</b>	0,40 m
<b>Four-wheel drive</b>	no
<b>Supports</b>	ja
<b>Support pressure max.</b>	21.8 kN
<b>Support on both sides LxW</b>	4.95 x 5.30 m
<b>Support one-sided BxL</b>	4.07 x 6.55 m
<b>Support narrow WxL</b>	3.11 x 6.55 m
<b>Swivel range</b>	+/- 225°
<b>Tractieaandrijving</b>	yes, white rubber chain
<b>Rotatable basket</b>	ja
<b>Indoor use only</b>	no
<b>Non-Marking</b>	ja
<b>Special features</b>	Variable outriggers, enormous reach, choice of electric or diesel drive, rental on request incl. transport trailer, total weight then 3,500 kg, chassis hydraulically height-adjustable for driving on slopes.



