

GSA 30 J

| | |
|--|---|
| Max. Working height | 30,20 m |
| Max. Basket load / Lifting load | 200 kg |
| Drive type | Hybrid |
| Max. lateral reach | 15,60 m |
| Overall dimensions LxWxH | 7.21 x 1.59 x 1.99 m |
| Transport position length | 7,21 m |
| Construction width | 1,59 m |
| Transport position height | 1,99 m |
| Platform dimensions WxD | 1.27 x 0.83 m |
| Swing axle | no |
| Basket arm, rotation angle | yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° |
| Dead weight | 4300 kg |
| Ground clearance | 0,02 / ab 50 cm 0,26 m |
| Four-wheel drive | no |
| Supports | ja |
| Support pressure max. | 26.0 kN |
| Support on both sides LxW | 6.35 x 6.04 m |
| Support one-sided BxL | 4.86 x 8.33 m |
| Support narrow WxL | 3.38 x 8.33 m |
| Swivel range | 450° |
| Tractieaandrijving | yes, white rubber chains |
| Rotatable basket | ja/180° ja/180° ja/180° ja/180° ja/180° ja/180° ja/180° |
| Indoor use only | no |
| Non-Marking | ja |
| Special features | Height 1.99 m with ground clearance of 0.02 m, overhang of 0.75 m with one-sided support, supportable up to terrain inclination of 30%, 2 PPE attachment points, basket changing device. Can be rented with transport truck on request, hydraulically height-adjustable |







