

# GSA 30 L

<b>Max. Working height</b>	30,02 m
<b>Max. Basket load / Lifting load</b>	400 kg
<b>Drive type</b>	Hybrid
<b>Max. lateral reach</b>	16,70 m
<b>Overall dimensions LxWxH</b>	7.82 x 1.58 x 1.98 m
<b>Transport position length</b>	7,82 m
<b>Construction width</b>	1,58 m
<b>Transport position height</b>	1,98 m
<b>Platform dimensions WxD</b>	1.32 x 0.96 m
<b>Swing axle</b>	no
<b>Basket arm, rotation angle</b>	yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180° yes/180°
<b>Dead weight</b>	4500 kg
<b>Ground clearance</b>	0,17 m
<b>Four-wheel drive</b>	no
<b>Supports</b>	ja
<b>Support pressure max.</b>	32 kN
<b>Support on both sides LxW</b>	6.35 x 6.04 m
<b>Support one-sided BxL</b>	4.86 x 8.33 m
<b>Support narrow WxL</b>	3.38 x 8.33 m
<b>Swivel range</b>	450°
<b>Tractieaandrijving</b>	yes, white rubber chain
<b>Rotatable basket</b>	ja
<b>Indoor use only</b>	no
<b>Non-Marking</b>	ja
<b>Special features</b>	Can also be used for material handling, max. lifting load then 400 kg. Earthing with earthing spike possible. For better handling of the machine, a removable counterweight is fitted as standard, which increases the tare weight of the machine to 4,830 kg.



