

## GTK 124-14 Wk

|                                        |                                     |
|----------------------------------------|-------------------------------------|
| <b>Max. Working height</b>             | 12,38 m                             |
| <b>Movable up to working height</b>    | 8,07 m                              |
| <b>Max. Pitch angle</b>                | 25 %                                |
| <b>Four-wheel drive</b>                | Chain drive                         |
| <b>Drive type</b>                      | Diesel/230V                         |
| <b>Non-Marking</b>                     | ja                                  |
| <b>Overall dimensions LxWxH</b>        | 4.09 x 1.41 (1.17 without basket) m |
| <b>Transport position length</b>       | 3,45 m                              |
| <b>Construction width</b>              | 1,41 m                              |
| <b>Transport position height</b>       | 1,99 m                              |
| <b>Surplus</b>                         | -                                   |
| <b>Ground clearance</b>                | 0,14 m                              |
| <b>Dead weight</b>                     | 2850 kg                             |
| <b>Track widening</b>                  | 1,98 m                              |
| <b>Platform dimensions WxD</b>         | 1.30 x 0.73 m                       |
| <b>Max. Basket load / Lifting load</b> | 230 kg                              |
| <b>Basket arm</b>                      | ja                                  |
| <b>Swivel range</b>                    | 2 x 110°                            |
| <b>Rotating work basket</b>            | ja                                  |
| <b>Max. lateral reach</b>              | 7,00 m                              |



